




SensoWash® C SensoWash Starck C shower-toilet seat # 610001001001300

< 14 5/8" Inch >



SensoWash Starck C shower-toilet seat	Dimension	Weight	Order number
<p>with concealed connections, remote control included, power actuated lid and seat, rear-, front and oscillating wash, individual adjustment of water-, air- and seat surface temperature as well as nozzle position and jet strength, self-cleaning wand, 2 individually programmable user profiles, night light, Quick release: easy seat unit removal and attachment, on / off-button, CIAPMO®ELECTRICAL</p>			
<p>Colors 00 White</p>			
<p>Variant</p>			
<p>AC 100 - 120V 50 - 60Hz</p>	<p>14 5/8" x 20 1/4" Inch</p>	<p>14.1 lb</p>	<p>610001001001300</p>
<p>Infobox Install a water water softener with water hardness ≥ 2.4 mmol/l ($\geq 14^\circ$ dH or 24° fH)., Suitable for selected Starck 2, Starck 3 und Darling New ceramics</p>			
<p>Suitable products</p>			
<p>Toilet wall-mounted washdown model, only in combination with SensoWash, connecting elements for SensoWash with concealed connections included, Durafix included, 14 5/8" x 24 3/8" Inch</p>	<p>14 5/8" x 24 3/8" Inch</p>		<p>254459</p>
<p>Toilet wall-mounted washdown model, cUPC listed, only in combination with SensoWash, connecting elements for SensoWash with concealed connections included, Durafix included, 14 5/8" x 24 3/8" Inch</p>	<p>14 5/8" x 24 3/8" Inch</p>		<p>222659</p>
<p>Toilet close-coupled (without tank), washdown model, only in combination with SensoWash, outlet for vario connector set, for horizontal and vertical outlet, length adjustable from 2 3/4" - 7 7/8", and vario connecting bend, vertical outlet from 7 1/2" - 9", 14 5/8" x 27 3/4" Inch connecting elements for SensoWash with concealed connections included, hardware included, cUPC listed, 14 5/8" x 27 3/4" Inch</p>			<p>214159</p>

SensoWash® C SensoWash Starck C shower-toilet seat # 610001001001300

| < 14 5/8" Inch > |

<p>Toilet close-coupled (without tank), washdown model, only in combination with SensoWash, outlet for vario connector set, for horizontal and vertical outlet, length adjustable from 2 3/4" - 7 7/8", and vario connecting bend, vertical outlet from 7 7/8" - 9 1/2", connecting elements for SensoWash with concealed connections included, hardware included, cUPC listed, 14 3/4" x 28 3/8" Inch</p>	<p>14 3/4" x 28 3/8" Inch</p>	<p>212959</p>
<p>Toilet wall-mounted washdown model, cUPC listed, only in combination with SensoWash, connecting elements for SensoWash with concealed connections included, Durafix included, 14 1/8" x 24 3/8" Inch</p>	<p>14 1/8" x 24 3/8" Inch</p>	<p>253359</p>
<p>Two-Piece toilet (without tank), US-version toilet, only in combination with SensoWash, syphonic, 12" rough-in, connecting elements for SensoWash with concealed connections included, vertical outlet, cUPC listed, 1.28 gpf, 14 5/8" x 27 1/2" Inch</p>	<p>14 5/8" x 27 1/2" Inch</p>	<p>212651</p>
<p>One-Piece toilet US-version toilet, only in combination with SensoWash, syphonic, 12" rough-in, with Single Flush piston valve, top flush, connecting elements for SensoWash with concealed connections included, vertical outlet, cUPC listed, 1.28 gpf, 15 3/4" x 28 1/8" Inch</p>	<p>15 3/4" x 28 1/8" Inch</p>	<p>212351</p>
<p>One-Piece toilet US-version toilet, only in combination with SensoWash, syphonic, 12" rough-in, with Single Flush mechanism, with side lever, 3" flapper valve, connecting elements for SensoWash with concealed connections included, vertical outlet, cUPC listed, 1.28 gpf, 14 5/8" x 28 1/8" Inch</p>	<p>14 5/8" x 28 1/8" Inch</p>	<p>212051</p>
<p>Two-Piece toilet (without tank), US-version toilet, only in combination with SensoWash, elongated, 12" rough-in, connecting elements for SensoWash with concealed connections included, vertical outlet, cUPC listed, 1.28 gpf, 14 5/8" x 27 3/4" Inch</p>	<p>14 5/8" x 27 3/4" Inch</p>	<p>212551</p>
<p>One-Piece toilet US-version toilet, only in combination with SensoWash, syphonic, 12" rough-in, with Single Flush piston valve, top flush, connecting elements for SensoWash with concealed connections included, vertical outlet, cUPC listed, 1.28 gpf, 14 3/4" x 28 1/8" Inch</p>	<p>14 3/4" x 28 1/8" Inch</p>	<p>213351</p>

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in inch & mm and are non-binding. Exact measurements, in particular for customized installation scenarios, can only be taken from the finished ceramic piece.