

Collection:Phineas

Installation manual for:

LD7015C W42"*H8.4"*E5.8"L5

Installation instructions:

- 1. Black wire from ceiling(junction box) attaches to "L"wire from the fixture.
- 2. White wire from ceiling(junction box) attaches to "N"wire from the fixture.
- 3. "E" wire from the fixture is attaced to the mounting bracket and an additional "E" wire from the mounting bracket must be secured to the junction box.
- 4.Secure mounting bracket to the junction box.

 5.Insert screws (P2) in side of top unit the mounting bracket(P1).
- screw (P3) 6.Lock the lamp body on the mounting bracket (P1) on the wall with a flat head
- 7.Hang Crystal(P11) 8.Install E12 light source.(Bulbs not supplied)

The end!

PARTS LIST

• .	
Junction box	
P1 P2	
2 P3	
P4 P5	
P6	

P10		P9	P8 [P7	P6	P5 □	P4 ©	Р3 с	P2 m	P1	Part Pi	
							0 70	<u>Щ</u>			Picture	
	Flat iron frame (L3. 93"*\"3. 93"\"\10. 28")	E12 card type full tooth lamp head	Anti-edge light cup (Φ1.57"*H1.57"mm)	Cylindrical iron (Φ0.55″**HO.31″)	Square tube (0.59"*1.18"*T1.0*L39.76")	Double head tube (Ø0.37°°L3.03°mm)	Square box (L4.8″*\4.8″*\60.8″)	Flat head Screw	Mounting bracket screw	U-shaped hanging board (L4.53**W4.33***H0.59**)	Description	
	u	u	5	7	1	2	-	4	2	1	Ş	
											Check list	

[&]quot;L" = Hot wire
"N" = Neutral wire "E" = Ground wire