IVING ISTRICT


Collection: Atlas
Installation manual for:


LD7305W29BLK W28.5"x E7.5" x H4.8" L4

Install the E12 light bulb, Don't use halogen bulbs, Please use LED ball bulbs, Wattage within 5W.

Installation instructions:

- 1. Black wire from ceiling(junction box) attaches to "L"wire from the fixture.
- 2. White wire from ceiling(junction box) attaches to "N"wire from the fixture.
- 3. "E" wire from the fixture is attaced to the mounting bracket and an additional "E" wire from the mounting bracket must be secured to the junction box.
- 4. Secure mounting bracket to the junction box.
- 5.Insert the mounting bracket screw(P2) into the mounting bracket (P1)
- 6.Useing the nut(P3) to lock the lamp body onto the mounting bracket (P1) on the wall.
- 7.Use the socket ring(P8) to lock the aluminum hemisphere(P11) onto the lamp body
- 8.Install LED E12 ball light source.(MAX LED 5W, Bulbs not supplied)
- 9.Twist the Acrylic hemisphere(P12) onto the Aluminum hemisphere(P11) The end!





Part Number	Part	Picture	Description	Qty
MB7R03	P1		Mounting bracket Φ4"*H1.2"	1
	P2	ammin_j)	Mounting bracket screw	2
	P3		Nut	2
	P4		Backplate (Φ4.7"*H1")	1
P-LD7305W29BLK-1	P5		Double head tube (L26.3"*H1")	1
	P6		Socket Cup (Φ1.6"*H1.4")	4
	P7	—	E12 holder	4
	P8	4001	Socket rings	4
	P9	\ \	UL18#Ground wire,L9.8"	1
	P10	\approx	UL18#,L8"	1
GS7R16BK	P11		Aluminum hemisphere (Φ4.7"*H2.4")	4
	P12		Acrylic hemisphere (Φ4.7"*H2.4")	4

[&]quot;L" = Hot wire
"N" = Neutral wire
"E" = Ground wire