

KSF-2631

Single Handle Commercial Style Pull Down Sensor Kitchen Faucet

Faucet Dimensions

Overall Height: 21 7/8"
 Spout Height: 8 1/4"
 Spout Reach: 9 1/8"

*Deck Plate Dimensions

Overall Dimensions: 10 1/4" x 2 1/2" x 1/4"

Features

- Commercial Style Pull Down Sensor Faucet
- Metal Body & ABS Sprayer
- Lead Free Waterway
- 360° Swivel Spout
- Flow Rate: 1.75 gpm (6.6L/min) @ 60 psi
- Spray Type: Dual Function Spray/Stream
- 35mm Ceramic Cartridge
- Dome Shaped Screen Washer
- Swivel Sprayer Connector
- 16" Hose Length
- Quick Weight
- Quick Connect Sprayer Hose
- 26 3/4" Integrated Nylon Waterlines
- Connections 3/8" Compression
- Max Deck Thickness: 3 1/8"
- TPI of aerator in the Sprayer - M16.5*1

Accessories Included

- *Deck Plate
- Hex Wrench
- Weight
- Control Box
- Battery & Battery Housing
- AC Adapter (Optional, sold separately)

Available Finishes

- Matte Black
- Spot Free Stainless Steel
- Spot Free Antique Champagne Bronze

CODES/STANDARDS:

Product Certification

cUPC (ASME A112.18.1/CSA B125.1)
 NSF/ANSI Standard 61 and 372 certified by IAPMO
 AB1953, MASS, DOE, CEC, ADA

NOTE: Some Kitchen Faucets that do not have a pull out or pull down sprayer may be connected to a portable dishwasher. Pull out and pull down faucets should never be connected to portable dishwashers because potential pressure fluctuations during washing cycles cause hose ruptures or leaks.

Warranty

Kraus Limited Lifetime Warranty
 see website for details www.kraususa.com

